

MOTh

Use

Amt. Req.	Size and Description PLYWOOD	Use
4	1/4 x 48 x 96" fir XT AB or AC plywood (*For lightweight models, substitute 1/4", 3-ply, Mufumbi mahogany plywood. Available, FOB, Harbor Sales, 1501 S. Warner, Baltimore 21230, Md.).	planks, decks, transom, spars

(Parentheses indicate stock sizes used when ordering only)

1	(1x4) x 16' spruce* or fir	mast, moldings
5½	(1x4) x 12' spruce or fir	frames, keelson, tiller, boom
1	(1x6) x 8' spruce or fir	fram #3
1	(1x10) x 8' spruce or fir	daggerboard, rudder blade
2	(2x4) x 12' spruce or fir	mast filler, upper stem, form legs
1	(2x6) x 12' spruce or fir	building form, stem

3 lbs. 1" ringed nails (Maze or Everdure* Stronghold)

9 doz. #6 x 1" fh brass screws

4 doz. #8 x 1" fh galvanized or brass* screws

6 doz. #8 x 1 3/4" fh galvanized or brass screws

8 1/4 x 4" carriage bolts, nuts, flat washers

10 1/4 x 3" carriage bolts, nuts, flat washers

4 1/4 x 1 1/2" fh stove bolts

2 $\frac{1}{8}$ x $\frac{3}{4}$ x 2" galvanized angle braces

1 pt. Kuhl's Rub-R-Tex bedding compound

3 lbs. Weldwood glue powder

*Materials recommended for class-racing models.
Available. Alan-Clarke Co., 235 Main St., Northport,
N.Y. 11768

