

# INTERNATIONAL NONSUCH ASSOCIATION SPECIFICATIONS

## 1. SAIL PLANS (MAXIMUM DIMENSIONS)

|                                                                        | NS-22 | NS-26<br>& 260 | NS-30 | NS324 | NS-33<br>& 354 | NS-36 |
|------------------------------------------------------------------------|-------|----------------|-------|-------|----------------|-------|
| Luff (Hoist)                                                           | 34.0' | 41.0'          | 45.0' | 48.0' | 50.5'          | 53.0' |
| LP at CLEW                                                             | 18.0' | 20.5'          | 24.0' | 24.0' | 26.5'          | 28.0' |
| Distance from<br><b>head point</b> to<br>upper leech<br>point, minimum | 8.5'  | 10.6'          | 11.8' | 12.6' | 13.25'         | 13.9' |
| LP at upper<br>leech point                                             | 6.2'  | 7.0'           | 7.9'  | 8.4'  | 8.91'          | 9.6'  |

The rules to be used in measuring Nonsuch sails are those specified in the **current** ISAF Equipment Rules of Sailing.

## 2. TANKAGE REQUIRED (MINIMUM IN U.S. GALLONS)

|       | NS-22 | NS-26<br>& 260 | NS-30<br>& 324 | NS-33<br>& 354 | NS-36 |
|-------|-------|----------------|----------------|----------------|-------|
| Water | 8     | 30             | 40             | 50             | 56    |
| Fuel  | 6     | 12             | 14             | 20             | 24    |

## COMMITTEE:

Jon Ayers 317 Bay Ave., Huntington, NY 11743-1136  
 Allen Ames 19 West Hills Road Ivoryton, CT 06442  
 Graeme Hayward 400 Randall St., Oakville, ON L6J 6G1