

O'DAY 22-1980 & FUTURE MODELS

\*GENERAL

No specifications to be altered without approval from O'Day.

Window material 0.20 thickness equal to Howe and Bainbridge Plastipane.

Warranty number to be printed on each sail.

Sail label to O'Day design.

Sail Bags - a. All white with O'Day label on outside. Shipped in plastic bag to prevent sails from getting dirty.

b. Main and Jib in one bag marked accordingly. Spinnaker and Genoa in separate bags and each labelled accordingly. Genoa bag gives Genoa size.

c. Bag is synthetic with dacron drawstring large enough to hold sail when not folded.

All measurements will be made using the straight line extension method (apex) with the point of measurement taken where the two lines cross, unless the class rules specifically say to the contrary. All measurements +0 -2".

MAINSAIL

Material: 3.8 oz polyester from approved source

Dimensions: Luff: 24' - 6"  
Foot: 9' - 0"  
Leach: 25' - 9"

Headboard: 4" maximum

Battens: No. 1. 24"  
2. 30"  
3. 24"  
with elastic in ends of pockets

Tack: 148 machine sewn

Cunningham eye: 148 machine sewn 8" above tack.  
Clew: 148 machine sewn with small teflon outhaul slide  
Cutback: None  
Insignia: Dark Blue circle Outer Dia. 18" Inner Dia. 5 $\frac{1}{2}$ ", enclosing numerals '20' - 4" high, white. Back-to-back.  
Luff Finishing: 3" tape around 1" rope.  
13 pcs. 'O' eyelets with 3/8" nylon slugs  
Foot Finishing: 3" tape around 1-1/8" rope  
Tell Tails: 2 sets positioned as per O'Day requirements

JIB

Material: 5.0 oz polyester fabric from approved source  
Dimensions: Luff: 21' - 9"  
Foot: 8' - 2"  
Leach: 19' - 2"  
Head Finishing: 149 machine sewn  
Tack: 3/4" thimble with 1" nylon webbing 5 mm rope  
hand sewn around thimble, SS. shackle attached  
to thimble.  
Clew: 149 machine sewn  
Window: 1 pc. small tell tail, 1 pc. vision window 37" x 8"  
Leach Line: 2.5 mm 'O' eyelets and 2 pcs. nylon buttons  
Luff tape: 2 $\frac{1}{2}$ " around 5 mm rope (3-strand)  
Hanks: 9 pcs. 'O' hanks and 'O' eyelets

GENOA  
(160%)

Material: 3.8 oz polyester fabric from approved source

Dimensions:            Luff: 21' 9"  
                          L.P.: 11' 7"  
                          Leach: 20' 4½"  
  
Head Finishing: 149 machine sewn  
  
Tack:                   #3 thimble with rope hand sewn around with  
                          S.S. shackle attached.  
  
Cunningham eye: 149 machine sewn  
  
Clew:                   149 machine sewn  
  
Window:                1 vision window 37" x 8"  
                         1 tell tail small  
  
Leach line:           2.5mm '0' eyelets 2 pcs. Nylon button  
  
Luff tape:            3" around 5 mm rope (3-strand)  
  
Hanks:                7 pcs. '0' hanks with '0' eyelets

SPINNAKER

Material:            3/4 oz nylon ripstop arranged in approximate  
                          1/3 portions of red, white and blue.  
  
Dimensions:           Luff 23'-8½", foot 13' - 11½"  
  
Head:                149 machine sewn  
  
Tack/Clew:           149 machine sewn  
  
Luff tape:           1½" red and green soft nylon tape  
  
Foot tape:           1½" white polyester tape  
  
Design:              Radial Head

\*\*\*\*\*