

1971 & FUTURE

O'DAY 23

*GENERAL

No specifications to be altered without written approval from O'Day.

Window material .020 thickness equal to Howe and Bainbridge Plastipane.

Warranty number to be printed on each sail.

Sail label to O'Day design.

Sail Bags - a. All white with O'Day label on outside. Shipped in a plastic bag to prevent sails from getting dirty.
b. Main and Jib in separate bags and marked accordingly. Spinnaker and Genoa each in separate bags and each labelled accordingly. Genoa bag gives Genoa size.
c. Bag is synthetic with dacron drawstring large enough to hold sail when not folded.

All measurements will be made using the straight line extension method (apex) with the point of measurement taken where the two lines cross, unless the class rules specifically say to the contrary. All measurements +0 -2".

MAINSAIL

Material: 5 oz polyester fabric from approved source

Dimensions: Luff: 23' 6"
Foot: 9' 0"
Leach: 24' 10"

Headboard: 4" maximum

Battens: No. 1 16"
2 24½"
3 24½"
4 22½"

with elastic in ends of pockets

Tack: 149 machine sewn
Cunningham eye: 149 machine sewn 8" above tack
Clew: 149 machine sewn with small teflon outhaul slide.
Cutback: None
Luff: 3" tape around 1" rope 14 pcs. '0' eyelets with 3/8" slugs and 5/8" nylon shackles
Foot: 3" tape around 1-1/8" polypropylene rope
Insignia: Blue circle 21" O.D. 6½" I.D. enclosing white '23' numerals 5" high. Back-to-back.
Leach Line: 2.5mm with '0' eyelets and nylon clam cleat
Tell Tails: 2 sets positioned as per O'Day requirements

JIB

Material: 5 oz polyester fabric from approved source
Dimensions: Luff: 26' 3"
Foot: 11' 4"
Leach: 22' 0"
Head Finishing: 149 machine sewn
Tack: #3 thimble with 5mm rope hand sewn around and S.S. shackle attached.
Window: 1 pc. small tell tail window.
Leach line: 2mm '0' eyelets, 2 pcs nylon buttons.
Luff tape: 3" around 5mm 3-strand rope
Hanks: 9 pcs. '0' hanks with '0' eyelets

GENOA (150%)

Material: 3.8 oz polyester fabric from approved source

Dimensions: Luff: 28' - 9"
LP: 15' - 0"
Leach: 25' - 8"

Head Finishing: 149 machine sewn

Tack: #3 thimble with 5mm rope spliced around and S.S. 'shackle attached.

Clew: PG 30

Window: 1 pc. small tell-tail window

Leach line: 2mm '0' eyelets, 2 pcs. nylon button

Luff tape: 3" around 5mm 3-strand rope

Hanks: 9 pcs. '0' hanks with '0' eyelets

SPINNAKER

Tri Radial Design
S.L. = 28'3"

S.F. = 18'0"

.75 oz. nylon
Red/White/Blue
#149 all corners

1 $\frac{1}{4}$ " red and green nylon tape