

O'Day 272

STANDARD BOAT DESCRIPTION

1987

All O'Day boats are constantly being reviewed and improved. As a result, standard equipment and options are subject to change at any time. See your dealer for the latest specifications.

HULL AND DECK

- One piece, hand-laminated hull with molded sheer and boot stripes.
- 1,930 pound external lead keel bolted to keel stub/bilge sump molded with hull. Keel is high lift winged design.
- Swim/boarding platform molded into transom.
- Stainless steel swim ladder mounted on platform.
- Transom mounted fiberglass and foam rudder; epoxy coated tiller.
- Multi-position outboard bracket mounted on transom.
- Hull/deck joint is lapped, sealed with a marine adhesive/sealant, mechanically fastened and covered with an aluminum and vinyl gunwale guard.
- Hand laminated, balsa-cored deck with molded nonskid and two-tone colors. Plywood replaces balsa in high-stress areas.
- Fixed plexiglass ports.
- Two opening cabin ports.
- Fixed port from cockpit to quarterberth.
- Fixed skylight over main cabin.
- Translucent forward hatch.
- Anchor and rode locker in foredeck.
- Molded fiberglass toerails with teak caps.
- Stainless steel bow pulpit; stanchions with single life lines and pelican hooks; split stern pulpit.
- 2 ea. bow and 2 ea. stern 7" mooring cleats.
- Teak cabin top handrails on custom molded bases.
- Cockpit fuel tank locker.
- Cockpit sail/gear locker.
- Molded small items bin in taff-rail.
- Sliding companionway hatch with teak plywood penboards.
- Cabin top mounted Barlow 15 halyard/mainsheet winch.
- Mainsheet traveler mounted on cabin top; sheet led to cabin top winch and stopper.
- Barlow 16LTC genoa winches.
- Genoa track (1" x 5') with lead blocks.

SPARS AND RIGGING

- Anodized aluminum mast and boom.
- 130% vertical cut reefable genoa with UV cover.
- Mainsail with single reef.
- Single spreader, masthead rig with 1 x 19 stainless steel cable stays; swaged turnbuckles. Mast stepped on deck with hinged mast step.
- Mast running light and anchor light.

- Braided dacron, color coded rigging. Blue for mainsail; red for jib.
- Single line reef system led to cockpit allows quick reefing without going forward.
- Adjustable boom topping lift.
- Internal halyards, outhaul and reef.
- Cruising Design over the headstay furling system with control line led to cockpit.

INTERIOR

- Molded fiberglass floor pan extends throughout the interior; bonded to hull at two levels to increase stiffness and strength of hull; textured sole.
- Sound absorbing fabric headliner throughout interior.
- Fabric hull liner.
- Teak bulkheads and cabinets throughout interior.
- High-pressure laminate in off-white on counter and table tops.

V-BERTH

- 6'10" V-berth with storage under; 4" fabric covered foam cushions.
- Removable berth insert provides standing space.
- Folding privacy doors.
- Storage under berth.

HEAD

- Molded fiberglass vanity with sink, manual water pump, storage locker; and medicine/linen cabinet.
- Portable chemical head mounted.
- Hanging locker.

MAIN CABIN

- Facing settees in main cabin. Port settee is 6'3"; starboard is 5'6". Four-inch fabric covered foam cushion.
- Varnished teak and holly cabin sole hatches.
- Drop-leaf, bulkhead mounted table; folds to store when not in use.
- Galley with deep stainless steel sink; manual water pump; 3.0 cubic foot icebox; food and dish lockers; space for stove.
- Teak companionway ladder.
- Storage locker aft of port settee.
- Large double quarter berth, 7'6" long by 4' wide; 3" fabric covered foam cushion.
- Headroom 6'2" under companionway hatch—6' at forward end of companionway; 5'10" at main bulkhead.

MECHANICAL AND ELECTRICAL

- International running lights mounted on pulpits.
- 12 volt circuit breaker panel.
- Plastic battery box (battery not included).
- 30 gallon seamless plastic water tank with deck fill.
- Lightning ground system.
- Manual bilge pump.

EQUIPMENT

MAIN SAIL

GENOA SAIL

MAIN SAIL COVER

ROLLER FURLING SYSTEM

TILLER COVER

COCKPIT SHEET BAG

SUN SHADE

BOOM VANG

SOLAR POWER VENT

CIGARETTE LIGHTER / 12VOLT COMPASS

WINCH HANDLE

MANUAL BILGE PUMP

FIRE EXTINGUISHERS (2)

DOCK LINES

BATTERY

INBOARD DIESEL

MARINE HEAD W/HOLDING TANK CRADLE

PLEXIGLASS HATCHBOARDS

TEAK HATCHBOARDS

VHF MARINE RADIO

\$23,970.00

CHALET MARINE

3132 LAKE AVENUE

WILMETTE, IL. 60091

Tel: 708-256-0561

FAX: 708-256-4978

CHALET MARINE SALES

800 WATER STREET

AT AZARIAN MARINA

RACINE, WI. 53401

Tel: 414-632-0077

STANDARD BOAT DESCRIPTION O'DAY 272

DIMENSIONS AND CAPACITIES

HULL

	HULL	RIG
• LOA	26'11"	• I 30'10"
• LWL	22'11"	• J 10'6"
• Beam	9'0"	• P 26'1"
• Draft	.2'11"	• E 10'6"
• Ballast	1930 lbs.	
• Displacement	outboard 5025 lbs. inboard 5375 lbs.	

SAIL AREA

• Mainsail	136.9 sq. ft.
• 130% Genoa	220 sq. ft.

Mast Head above DWL 34'10"

CAPACITIES

• Berths	5
• Fresh Water	30 gallons
• Icebox	3.0 Cubic Feet
• Optional Fuel Tank (Inboard Engine)	9 gallons
• Optional Inboard Engine 10 HP Westerbeke, 2 Cylinder, Freshwater Cooled Diesel Engine	

