

WIDGEONMAINSAIL

Material: 3 oz. Dacron from approved suppliers.

Dimensions: Luff: 15' 6" +0" - 4"
 Leach: 16' 5" +0" - 4"
 Foot: 8' 1" +0" - 4"
 1/2 height 5' 0" +0" - 4"
 1/4 height
 Max. foot roach 4½"

Headboard: 4"

Battens: 1 @ 12"
 2 @ 18"
 3 @ 12"
 With elastic in ends.

Rope: 5/16" dia. for slotted luff only.

Foot: loose-footed

Tack: 5/8" I.D. handworked grommet.

Clew: 5/8" I.D. grommet handworked and leather bound.

Cutback: 2" x 8"

Insignia: Blue circle 12" O.D., 10" I.D. with red "W" in styling of O'Day literature. Placed back to back.

General: Loose-footed sail.

Sail bag: Synthetic with dacron drawstring, large enough to hold main and jib, marked with boat type and "main and jib".

JIB

Material: 3 oz. Dacron from approved suppliers.

Dimensions: Luff: 11' 0" +0" - 4"
 Leach: 10' 3" +0" - 4"
 Foot: 4'10" +0" - 4"
 Max. foot roach 4½"
 Leach straight or concave.

Luff Wire: 3/32" 7x7 stainless steel over stainless steel thimbles incorporating captive shackle equal to Fico FG 446 worked into tack thimble.

WIDGEON

JIB cont.

Hanks: 5 30mm at equal intervals. Top hank within 8" of head attached through "OO" spur toothed grommets.

Clew: 5/8" I.D. grommet handworked and leather bound.

Head: #1 spur toothed grommet in sail laced to wire thimble.

Sail bag: Packed with main.

SPINNAKER

Material: .75 oz. nylon ripstop.

Color: 1/3 red, 1/3 white, 1/3 blue.

Dimensions: Luffs 11' 0" max. 10' 8" min.
1/2 Foot 3' 6" max. 3' 4" min.
Head to Centre foot 11' 6" max. 11' 2" min.
1/2 Mid Girth 3' 10" max. 3' 6" min.
1/2 Quarter Girth 2' 8" max. 2' 4" min.
Measurements to be made in accordance with class rules.

Head: #2 spur toothed grommet leather bound.

Clews: #2 spur toothed grommet leather bound.

Sail bag: Synthetic with dacron drawstring, marked with boat type and "Spinn".