



SABRE YACHTS
SAILMAKER FACT SHEET FOR SABRE 32 SLOOP

November, 1985

Hull Numbers for Various Models:

1. Series I Hull Nos: 001 to present

Basic Rig Dimensions:

Series I:
P = 37.00' I = 42.08'
E = 10.83' J = 13.33'

Mainsail Data:

- | | |
|---------------------------------|--|
| 1. Main mast track | - #6 metalmast flat internal slides |
| 2. Main boom track | - Slotted internal track, $\frac{1}{2}$ " slugs |
| 3. Headboard shackle | - Schaefer 93-80 |
| 4. Main tack shackle | - Jaw opening $\frac{3}{4}$ ", jaw length 1" |
| 5. Set-back of tack | - $1\frac{1}{4}$ " from aft face of mast |
| 6. Set-up of tack | - $1\frac{1}{2}$ " above top of boom track |
| 7. Clew outhaul | - Shackle on slide: jaw opening $\frac{1}{2}$ ", jaw length 1", pin diameter $\frac{1}{4}$ ", set-up $1\frac{3}{4}$ " above boom track |
| 8. Luff slide stop | - Fitted 4" above black band |
| 9. Gooseneck | - Fixed |
| 10. Mast circumference | - $1' 7\frac{1}{2}"$ |
| 11. Boom circumference | - $1' 3"$ |
| 12. Jiffy reefing | - Two sets of jiffy reefing hardware are provided standard with each boat; use external rings for reef tacks. |
| 13. Set-back of reef tack hooks | - 2" from aft face of mast |

Headsail Data:

- | | |
|--|--|
| 1. Headstay diameter | - $\frac{9}{32}"$ |
| 2. Headstay length
(pin to pin including turnbuckle $\frac{2}{3}$ open) | - a. Series I: $44' 1\frac{1}{2}"$ |
| 3. Turnbuckle length | - $1' 6"$ extended |
| 4. Halyard shackle | - Nicro Fico NF 11000 S |
| 5. Tack Shackle | - Nicro Fico NF 11000 P |
| 6. Set-back of tack | - $1\frac{1}{2}"$ aft of headstay |
| 7. Genoa tracks
($1\frac{1}{4}"$ x $\frac{3}{16}"$ T-track) | - Series I: 10' outboard track on toerail with after end $5' 0"$ from transom corner; 10' inboard track with after end $5' 0"$ from transom corner.
(See Series I sail plan). |

NOTE: All genoas must be cut to lead within the track lengths indicated on the sail plan. This permits use of the required genoa sheet sheet turning blocks and other standard hardware.