

- (b) The body of the sail shall consist of woven ply throughout. The ply fibres shall be of polyester.
- (c) The sail shall have four batten pockets in the leech.
- (d) The leech shall not extend beyond a straight line from the clew point to the intersection of the leech and the lower edge of the lower batten pocket.
- (e) The sail may include slab reefing with up to four points in the body of the sail.
- (f) The sail shall include luff and foot boltropes.
- *** (g) The following are permitted: Stitching, glues, tapes, corner eyes, reef eyes, headboard with fixings, cunningham eye or pulley, reinforcements, batten pocket elastic, batten pocket patches, flutter patches, chafing patches, batten pocket end caps, Mast and boom slides, leech line with cleat, two windows, tell tales, sail shape indicator stripes, sail numbers, national letters and class insignia, sailmaker labels, class royalty label, certification mark.

G.5.3 Dimensions

	minimum	maximum
(a) Leech Length	8892 mm	
(b) Upper Width 483 mm from head point.....	375 mm	
(c) Half Width	2282 mm	
(d) Three-Quarter Width	1396 mm	
(e) Weight of the Ply of the body of the sail	192 gr/m ²	
(f) Window area.....	0.3 m ²	
(g) Outside Batten Pocket Length:		
(i) Uppermost and lowermost pockets.....	805 mm	
(ii) Intermediate pockets.....	960 mm	
(h) Head Point to intersection of leech and centerline of uppermost batten pocket	1740 mm	
(i) Clew Point to intersection of leech and centerline of lowermost batten pocket	1740 mm	
(j) Tack Point to center of reef grommet parallel to the luff.....	900 mm	1100 mm
(k) Clew Point to center of reef grommet parallel to the leech.....	900 mm	1100 mm

G.6 Headsail

G.6.1 Construction

- (a) The construction shall be: soft sail, single-ply sail.
- (b) The body of the sail shall consist of woven ply throughout. The ply fibres shall be of polyester.

(c) The headsail shall have two or three batten pockets in the leech.

(d) The following are permitted: Stitching, glues, tapes, corner eyes, hanks, reinforcements, batten pocket elastic, batten pocket patches, flutter patches, batten pocket end caps, leech line with cleat, foot line with cleat, two windows, tell tales, sail shape indicator stripes, sheeting blocks, sailmaker labels, class royalty label, certification mark.

G.6.2 Dimensions

	minimum	maximum
(a) Luff Length.....	7240 mm	
(b) Leech Length.....	6477 mm	
(c) Luff Perpendicular.....	2515 mm	
(d) Foot Median.....	7000 mm	
(e) Half Width.....	1285 mm	
(f) Three Quarter Width.....	650 mm	
(g) Upper Width 183 mm from head point.....	102 mm	
(h) Weight of the ply of the body of the sail.....	188 gr/m ²	
(i) Window area.....	0.2 m ²	
(j) Outside Batten Pocket Length:		
(i) Top.....	335 mm	
(ii) Intermediate and/or bottom.....	430 mm	
(k) Head Point to intersection of leech and centreline of uppermost batten pocket.....	1580 mm	
(l) Clew Point to intersection of leech and centreline of lowermost batten pocket.....	1580 mm	

G.7 Spinnakers

G.7.1 Identification

(a) Numbers and national letters

- (i) Numbers and national letters shall conform to the RRS.
- (ii) The color shall be contrasting with the background.

G.7.2 Construction

(a) The construction shall be soft sail, single-ply sail.

(b) The body of the sail shall consist of woven ply throughout. The ply fibres shall be of polyamide.

***(c) The following are permitted: Stitching, glues, tapes, corner eyes, eyes, reinforcements, tell tales, sailmaker labels, class royalty label, sail identification, certification mark.

G.7.3 Dimensions

		minimum	maximum
(a) Leech Lengths.....	7467 mm	7620 mm	
(b) Foot Length.....	4700 mm	4800 mm	
(c) Foot Median.....		8850 mm	
(d) Difference between diagonals.....		50 mm	
(e) Half Width.....	4565 mm	4715 mm	
(f) Weight of the ply of the body of the sail.....	32 gr/m ²		

Part III – APPENDICES

Appendix A – Documents

Section H – Official Plans and Forms

H.1.1 Keel Plan designated KEEL-1

H.1.2 Rudder Plan designated RUDDER-1

H.1.3 Insignia Plan designated INSIGNIA-1

H.1.4 Certification Marks designated MARKS-1

H.1.5 Hull Measurement Form designated HMF-1

Appendix B – Alternative Rules

Rules or modifications within this appendix apply to SCA, IFDS or Disabled Sailing National Authority sanctioned events designated as an “SCA Appendix B – Alternative Rules” event.

Section I – Conditions for Racing

I.1 GENERAL

I.1.1 The Notice of Race shall state that “This is an SCA Appendix B – Alternative Rules event.”

I.1.2 Except as modified or amended in this appendix, the requirements of Parts I and II shall apply.

I.1.3 Modifications specifically permitted in this appendix must be easily removed so that the boat conforms to Part II of the class rules.

I.2 DEFINITIONS

I.2.1 **Disabled Sailor:** A person who is eligible, under the IFDS Functional Classification System, to compete in IFDS sanctioned or disabled sailing National Authority events and possesses a