

## Tanzer 22 Specifications

---

### Tanzer 22 Specifications

|                            |          |
|----------------------------|----------|
| L.O.A.                     | 22'-6"   |
| L.W.L.                     | 19'-9"   |
| Beam                       | 7'-10"   |
| Draft Fin Keel             | 3'-5"    |
| Draft Keel-Center Board Up | 2'-0"    |
| Down                       | 4'-0"    |
| Displacement               |          |
| Fin Keel                   | 2900 lbs |
| Keel-C/B                   | 3100 lbs |
| Ballast Fin Keel           | 1250 lbs |
| Keel-C/B                   | 1500 lbs |
| Vertical clearance         | 31'-0"   |

---

### Tanzer 22 Rigging Data

Standing Rigging - All 1x19 S/S type 302

Forestay (5/32"), T/B 2/3 open +toggle = 28'-6 3/8"

Backstay (5/32"), T/B 1/3 open + toggle = 30'-7 1/4"

Uppers (5/32"), T/B 2/3 open + toggle = 27'-1 7/8"

Lowers (5/32"), T/B 1/2 open + toggle = 13'-8 1/8"

---

### Running Rigging

Main Halyard - 25'-9" of 3/32" 7x19 (or 7x7) wire from shackle to thimble plus 28'-0" of 5/16" Dacron tail

Jib Halyard - 25'-9" of 1/" 7x19 wire from shackle to thimble plus 28'-0" of 5/16" Dacron tail

Topping Lift - 25'-0" of 3/32" 1x19 (or 7x19) wire (Thimble to Thimble length)

Spinnaker Halyard - 68'-0" of 5/16" Dacron.

Spinnaker Pole topping (Uphaul) - 35'-0" of 5/16" Dacron.

Foreguy (Pole downhaul) - 25'-0" of 5/16" Dacron.

Spinnaker sheets - 2x 45'-0" of 5/16" Dacron braid.

Mainsheet - 60'-0" of 3/8" Dacron braid

Genoa sheets - 2x 35'-0" or 1x 68'-0" of 7/16" Dacron

Jib Sheets - 2x 26'-0" or 1x 50'-0" of 3/8" Dacron

Boom Vang - 21'-0" of 5/16" Dacron

Note: All Sheets to be Dacron double braid - Halyards can be double braid or 3-strand Dacron.

---

#### Rig Dimensions

I = 28.43', J = 8.56', P = 23.0', E = 9.0'

Spinnaker Pole length = 8'-9", Diameter = 2"

---

[\[Tanzer 22 Home Page\]](#) [\[Parts\]](#) [\[E-mail list\]](#) [\[Regattas\]](#)

---

Copyright © 1995-1996 Serge Alfaro. All rights reserved.