

Specifications for the Potter 15 and Potter 19



DESIGNERS

Potter 15
Potter 19

Stanley T. Smith
Herb E. Stewart



ROPE LENGTHS

	P-15	P-19
Main Halyard	36'	37'
Jib Halyard	28'	37'
Genoa Halyard	28'	35'
Spinnaker Halyard	28'	35'
Main Sheet	27'	31'
Jib Sheet	34'	37'
Genoa Sheet	34'	37'
Spinnaker sheets (2)	18'	22'
Spin. Topping Lift (1/8")	18'	19'
Spin. Down Haul (1/8")	4.5'	10'
Topping Lift (1/8")	30'	42'
Boom Outhaul	4.5'	4'
Boom Down Haul	3.5'	3'
Boom Vang	11'	12'
Keel Lift Line	12'	26-28' cable
Jiffy Reefing Line	16.5'	14'
Reef Ties	2.5'	2.5'
Spinnaker Pole Length	64"	7'



STANDING RIGGING LENGTHS

	P-15	P-19	P-19 short rig
Backstay	--	293"	--
Forestay	146"	216"	173"
Sidestays (upper)	148 5/8"	224 1/4"	172"
Sidestays (lower)	--	130 1/8"	--



BOAT SPECIFICATIONS

	P-15	P-19
Length Overall	15' 0"	18' 9"
Length waterline	12' 0"	16' 9"
Beam	5' 6"	7' 6"
Draft		
Keel Up	6"	6"
Keel Down	3' 0"	3' 7"
Keel Weight	100#	370#
Boat Weight w/ Keel	475#	1225#
Trailer Weight	200#	300#
Trailer Tongue Weight	45#	120##
Aft Cabin Height	3' 9"	5' 0"
Berths	2	4
Motor Capacity	2-4 hp	2-6 hp
Mast Height above deck	15' 6"	22' 0"



SAIL AREA

	P-15	P-19
Main	64	83
Jib	23	52
Lapper	--	76
Genoa	43	107
Spinnaker	85	207



SAIL MEASUREMENTS

	P-15	P-19
I	15' 6"	22' 0"
J	4' 7"	7' 0"
P	13' 6"	19' 10"
E	8' 3"	8' 0"

Sail slug sizes: 7/16"



P-15 TRAILER

Hitch Size	1 7/8" ball
Electrical	4-prong flat plug
Tire/Wheel	4.80-8LRB
Inflation (varies)	60 psi
Max. Carrying Cap.	800#